



Available Ink Configurations

Green (G) and orange (O) inks have been eliminated from the GX and GO ink set configurations. The chart below illustrates all remaining ink set combinations.

NOTE 1: If the use of a six (6) color ink set is desired, cartridges must be installed in carriage stall positions indicated by an asterisk (*). Typically the standard YMCK colors are used in these locations; ink bottles and cartridges need to be primed and working correctly in these 'unused' locations. While the stall positions are not used during printing they are used during routine spitting (i.e. every 6, 15, or 120 second spit intervals depending on ink type and spit routine selected). An 'Out of Ink or Deprime' error message may result if cartridges in these stall positions are not primed properly as outlined above.

CARTRIDGE STALL									
Ink Set	4	3	2	1		Y	M	C	K
GS+	M _L	C _L	M _M	C _M		Y	M	C	K
GS+	*	*	M _M	C _M		Y	M	C	K
GS+	Y	M	C	K		Y	M	C	K
GX	M _L	C _L	M _M	C _M		Y	M	C	K
GX	*	*	M _M	C _M		Y	M	C	K
GX	G	O	*	*		Y	M	C	K
GX	G	O	M_M	C_M		Y	M	C	K
GX	Y	M	C	K		Y	M	C	K
GO+	*	*	M _M	C _M		Y	M	C	K
GO+	G	O	*	*		Y	M	C	K
GO+	G	O	M_M	C_M		Y	M	C	K
GO+	Y	M	C	K		Y	M	C	K

* If you plan on using a six-color configuration, you will still need to select the 1x8 Cartridge Set and install valid cartridges in the two stalls you are not using.

NOTE 2: The Kodak 4800 series printers originally used light fast (LF) dye inks which follow the same configurations as GS+ above. The LF pigment inks were only available in the CMYK ink configuration, but are no longer available. Kodak 4800 customers who wish to use Encad inks/cartridges should upgrade printer firmware (NJ8x2013.rom).